



1. Chemical product and company identification

Product name RUSTILO 4135 HF
Code 09016-AE
Product use Corrosion inhibitor.
Manufacturer Castrol Industrial North America, Inc.
 150 W. Warrenville Road
 Naperville, IL 60563
Supplier Castrol Industrial North America, Inc.
 150 W. Warrenville Road
 Naperville, IL 60563
 Product Information: 1-800-621-2661
EMERGENCY SPILL INFORMATION: 1 (800) 424-9300 CHEMTREC (USA)

2. Composition/information on ingredients

Ingredient name	CAS #	% by weight
Distillates (petroleum), hydrotreated light paraffinic (Hydrocarbon solvent)	64742-47-8	85 - 90
Refined paraffin wax	8002-74-2	1 - 5

3. Hazards identification

Physical state Liquid.
Color Clear. Amber.
Emergency overview WARNING!
 ASPIRATION HAZARD.
 Harmful or fatal if liquid is aspirated into lungs.
 MAY CAUSE EYE IRRITATION.
 MAY CAUSE SKIN IRRITATION.
 MAY CAUSE RESPIRATORY TRACT IRRITATION.
 Do not ingest. Do not get in eyes, on skin or clothing. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling.
Routes of entry Dermal contact. Eye contact. Inhalation. Ingestion.
Potential health effects
Eyes May cause eye irritation.
Skin May cause skin irritation. Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Inhalation May cause respiratory tract irritation.
Ingestion Ingestion may cause gastrointestinal irritation and diarrhea.
 Aspiration hazard if swallowed -- harmful or fatal if liquid is aspirated into lungs.
Medical conditions aggravated by over-exposure None identified.

Product name RUSTILO 4135 HF	MSDS # 09016-AE	Page: 1/5
Version 4	Date of issue 12/13/2005.	Format US
		Language ENGLISH. (ENGLISH)
	Build 4.2.6	

4. First aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation develops.
Skin contact	Immediately wash exposed skin with soap and water. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention if irritation develops.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if irritation develops.
Ingestion	If swallowed, do NOT induce vomiting. Never give anything by mouth to an unconscious person. Aspiration hazard if swallowed- can enter lungs and cause damage. Get medical attention.

5. Fire-fighting measures

Flammability of the product	May be combustible at high temperature.
Flash point	112.78 °C (Open cup) Cleveland. 112 °C (Closed cup)
Products of combustion	These products are carbon oxides (CO, CO ₂).
Unusual fire/explosion hazards	This material is not explosive as defined by established regulatory criteria.
Fire-fighting media and instructions	In case of fire, use water fog, foam, dry chemicals, or carbon dioxide.
Protective clothing (fire)	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

6. Accidental release measures

Personal precautions	Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (See Section: "Exposure controls/personal protection"). Follow all fire fighting procedures (See Section: "Fire-fighting measures").
Environmental precautions and clean-up methods	If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal. Avoid contact of spilled material with soil and prevent runoff entering surface waterways. See Section 13 for Waste Disposal Information.
Personal protection in case of a large spill	Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

7. Handling and storage

Handling	Do not ingest. Do not get in eyes, on skin or on clothing. Avoid contact with skin and clothing. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable. Use only with adequate ventilation. Wash thoroughly after handling.
Storage	Keep container tightly closed. Keep container in a cool, well-ventilated area. Empty containers may contain harmful, flammable/combustible or explosive residue or vapors. Do not cut, grind, drill, weld, reuse or dispose of containers unless adequate precautions are taken against these hazards.

Product name RUSTILO 4135 HF	MSDS # 09016-AE	Page: 2/5
Version 4	Date of issue 12/13/2005.	Format US
		Language ENGLISH.
	Build 4.2.6	(ENGLISH)

8. Exposure controls/personal protection

Occupational exposure limits

Ingredient name

Distillates (petroleum), hydrotreated light paraffinic (Hydrocarbon solvent)
Refined paraffin wax

Occupational exposure limits

ACGIH TLV (United States, 1/2004). Skin
TWA: 200 mg/m³ 8 hour(s).
ACGIH TLV (United States, 1/2005).
TWA: 2 mg/m³ 8 hour(s). Form: Fume

Control Measures

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Personal protection

Eyes

Avoid contact with eyes. Safety glasses with side shields.

Skin and body

Avoid contact with skin and clothing. Wear suitable protective clothing.

Respiratory

Use only with adequate ventilation. In accordance with good industrial hygiene and safety work practices, airborne exposures should be controlled to the lowest extent practicable.

Hands

Wear suitable gloves.

Not available.



Consult local authorities for acceptable exposure limits.

9. Physical and chemical properties

Physical state

Liquid.

Odor

Mild.

Color

Clear. Amber.

Specific gravity

0.8 to 0.85

Solubility

Insoluble in cold water.

Viscosity

Kinematic: <7 mm²/s (<7 cSt) at 40°C
SUS: 35 to 38 SUS at 37.778°C

10. Stability and reactivity

Stability and reactivity

The product is stable.

Conditions to avoid

Not available.

Incompatibility with various substances

Not available.

Hazardous decomposition products

Not available.

Hazardous polymerization

Will not occur.

11. Toxicological information

Chronic toxicity

Carcinogenic effects

No component of this product at levels greater than 0.1% is identified as a carcinogen by ACGIH or the International Agency for Research on Cancer (IARC). No component of this product present at levels greater than 0.1% is identified as a carcinogen by the U.S. National Toxicology Program (NTP) or the U.S. Occupational Safety and Health Act (OSHA).

Mutagenic effects

No component of this product at levels greater than 0.1% is classified by established regulatory criteria as a mutagen.

Reproductive effects

No component of this product at levels greater than 0.1% is classified by established regulatory criteria as a reproductive toxin.

Teratogenic effects

No component of this product at levels greater than 0.1% is classified by established regulatory criteria as teratogenic or embryotoxic.

12. Ecological information

Ecotoxicity

No testing has been performed by the manufacturer.

13. Disposal considerations

Waste information

Avoid contact of spilled material and runoff with soil and surface waterways. Consult an environmental professional to determine if local, regional or national regulations would classify spilled or contaminated materials as hazardous waste. Use only approved transporters, recyclers, treatment, storage or disposal facilities. Dispose of in accordance with all applicable local and national regulations.

[Consult your local or regional authorities.](#)

14. Transport information

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO)

15. Regulatory information

U.S. Federal regulations

US INVENTORY (TSCA): In compliance.

TSCA 12(b) one-time export notification:: dipropylene glycol methyl ether

This product is not regulated under Section 302 of SARA and 40 CFR Part 355.

SARA 311/312 MSDS distribution - chemical inventory - hazard identification: RUSTILO 4135 HF: Immediate (Acute) Health Hazard

SARA 313

Form R - Reporting requirements

This product does not contain any hazardous ingredients at or above regulated thresholds.

Supplier notification

This product does not contain any hazardous ingredients at or above regulated thresholds.

CERCLA Sections 102a/103 Hazardous Substances (40 CFR Part 302.4):: Methanol: 5000 lbs. (2268 kg);

State regulations

Massachusetts RTK: Refined paraffin wax; dipropylene glycol methyl ether

New Jersey: dipropylene glycol methyl ether

Pennsylvania RTK: Refined paraffin wax (generic environmental hazard); dipropylene glycol methyl ether (generic environmental hazard)

California prop. 65: No products were found.

Product name RUSTILO 4135 HF

MSDS #

09016-AE

Page: 4/5

Version 4

Date of issue 12/13/2005.

Format US

Language ENGLISH.

Build 4.2.6

(ENGLISH)

Inventories

AUSTRALIAN INVENTORY (AICS): In compliance.

CANADA INVENTORY (DSL): In compliance.

CHINA INVENTORY (IECS): In compliance.

EC INVENTORY (EINECS/ELINCS): In compliance.

JAPAN INVENTORY (ENCS): In compliance.

KOREA INVENTORY (ECL): In compliance.

PHILIPPINE INVENTORY (PICCS): In compliance.

16. Other information

Label requirements

WARNING!

ASPIRATION HAZARD.

Harmful or fatal if liquid is aspirated into lungs.

MAY CAUSE EYE IRRITATION.

MAY CAUSE SKIN IRRITATION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

HMIS® Rating :

Health 1 - **National Fire**
Flammability 1 **Protection**
Physical 0 **Association**
Hazard **(U.S.A.)**
Personal B
protection



Other special considerations

PETROLEUM OIL: STEL = 10 mg/M3. Using terminology of the International Agency for Research on Cancer (IARC), the petroleum distillates listed in Section II are classified by the supplier as severely processed. Not all those listed in Section II may be present. The supplier has stated that these distillates do not require a carcinogen label as defined by OSHA 29 CFR 1910.1200.

History

Date of issue

12/13/2005.

Date of previous issue

03/31/2005.

Prepared by

Product Stewardship

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from us.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken.

Product name RUSTILO 4135 HF

MSDS #

09016-AE

Page: 5/5

Version 4

Date of issue 12/13/2005.

Format US

Language ENGLISH.

Build 4.2.6

(ENGLISH)